



The most productive large-format color MFP¹—prints up to size E/A0



All your workflow needs in a highproductivity MFP

- Create D/A1-size pages in 21 seconds on the market's fastest, compact 36-inch MFP1
- Achieve dark blacks, true neutral grays, and vivid colors with Original HP inks
- Print out your first page right away thanks to ultra-fast processing and zero warm-up time
- Copy and scan quickly with advanced features—presets, batch scanning, multipage PDFs, and scan to email

A production printer for unattended, low-cost use

- Print your black-and-white drawings at the same cost per page as comparable black-and-white LED MFPs2
- Operate unattended thanks to two heavy rolls of up to 650 ft (200 m) and a total ink capacity of 1,800 ml
- Built for high-volume printing—rely on a robust design to fulfill the most demanding jobs
- Manage projects and control costs effectively, using embedded professional accounting features

End-to-end workflow efficiency

- Stay organized and avoid clutter—the integrated 100-page stacker delivers prints and copies neatly collated
- Manage PDFs, increase production, and cut job preparation time by up to 50% with HP SmartStream for DesignJet printers³
- HP Crystal Preview⁴ from HP SmartStream for DesignJet printers accurately shows how technical documents will be printed



Eco Highlights

- Half the energy consumption per plot than equivalent black-and-white LED MFPs¹
- ENERGY STAR® qualified and EPEAT Bronze registered²
- Free, convenient HP ink cartridge and printhead recycling³
- FSC®-certified papers and a range of recyclable HP media with a take-back program





- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per minute
- Explain the second of the seco information about HP large format printing materials, please visit globalBMG.com/hp.

Find out how at our website



- 1. With Aurasma installed, please go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 2. Without Aurasma installed, please download it:
 - a. Google Play http://auras.ma/s/android
 - b. Apple Store http://auras.ma/s/ios
 - Once done, go to the HP DesignJet channel at http://auras.ma/s/ke25m
- 3. Open the application and point to the image to view the HP DesignJet video

Technical specifications

Print				
riiiit	Line drawings ⁵	21 sec/page on A1/D, 120 A1/D prints per hour		
	Print resolution	Up to 2400 x 1200 optimized dpi		
	Margins (top x	Roll: 3 x 3 x 3 x 3 mm (0.12 x 0.12 x 0.12 x 0.12 in) (borderless on		
	bottom x left x right)	photo papers) Sheet: 3 x 22 x 3 x 3 mm (0.12 x 0.87 x 0.12 x 0.12 in)		
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)		
	Ink cartridges	6 (cyan, gray, magenta, matte black, photo black, yellow)		
	Line accuracy	+/- 0.1%6		
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)		
	Guaranteed	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁷		
	minimum line width			
Media	Handling	Input: two automatic front-loading roll feeds; smart roll switching; rolls up to 200 m (650 ft) long each and 180 mm (7.1 in) of diameter; sheet feed Output: integrated output stacker (from A4/A to A0/E, with up to 100 A1/D-size capacity); media bin; automatic cutter		
		Scanner: straight-through scan paper path for sheet and cardboard originals		
	Size	Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)		
	Thickness	Up to 0.5 mm (19.7 mil)		
Scan	Scan speed	Color: up to 6.35 cm/sec (2.5 in/sec)		
	Scan/ copy	Grayscale: up to 19.05 cm/sec (7.5 in/sec) Up to 600 dpi		
	resolution Maximum scan	Size: 914 x 8000 mm (36 x 315 in) (JPEG)		
	Maximum scan	914 x 5000 mm (36 x 197 in) (PDF) 610 x 15,000 mm (24 x 590.5 in) (TIFF)		
	Thickness	Up to 0.8 mm (0.03 in)		
Сору	Reduction/ enlargement	25 to 400%; at 1% increment		
	Maximum copies	Up to 99 copies		
	Copier settings	Copy quality, copy color, roll, paper output, content type, original pape type, background removal, contrast, de-skew, blueprints support,		
		copy margin layout, full width, job queue storage mode		
Applications		erings, Presentations, Maps, Orthophotos		
Memory	Intel Core i5M-260 processor, 128 GB (virtual),8 500 GB hard disk (AES-256 encrypted, FIP 140-2 Level 2 certified)			
Connectivity	Interfaces (standard)	High-Speed USB 2.0 certified host connector Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IR, Boote/DHCP (IPv4 only), DHCPv6, TFTP (IPv4o only), SNMP (v1 v2c, v3), Apple Bonjour Compatible, FTP, WS Discovery, Embedded		
		Web Server(HTTP, HTTPS), IPSec, SMTP (e-mail), Raw IP printing (9100, 9101, 9102), LPD, IPP, WS print, NTLM, NTLM v2, SSL/TLS, 802.1X authentication (WEP, WPA, WPA2, LEAP, PEAP, EAP-TLS)		
	Print languages	HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI		
	(standard) Print languages	Adobe PostScript 3; Adobe PDF 1.7		
	(optional) Printing paths	HP SmartStream software for HP DesignJet printers (optional), Printer		
		driver, HP Embedded Web Server, direct printing from USB flash drive,		
	Drivers (included)	email printing HP-GL/Z, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with		
Dimensions		email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit)		
Dimensions (w x d x h)	Printer	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in)		
		email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit)		
(w x d x h)	Printer Shipping	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS \times ; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) $1400 \times 784 \times 1109 \text{ mm} (55.1 \times 30.9 \times 43.7 \text{ in})$ $1502 \times 780.5 \times 804 \text{ mm} (59.1 \times 30.7 \times 31.7 \text{ in})$		
(w x d x h)	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac SX ½ PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 × 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 141 kg (251 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in		
(w x d x h) Weight What's in the box	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (r	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in <2), quick reference guide, setup poster, startup software, power cord		
(w x d x h) Weight	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)		
(w x d x h) Weight What's in the box Environmental	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, spindle adapter kit (s) Operating temperature Storage temperature	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in x2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F)		
(w x d x h) Weight What's in the box Environmental ranges	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (25.1 lb) 1411 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH		
(w x d x h) Weight What's in the box Environmental ranges	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, spindle adapter kit (soft operating temperature Storage temperature Operating humidity Sound pressure	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep)		
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 141 kg (310.8 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in (2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep)		
(w x d x h) Weight What's in the box Environmental ranges	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (25.1 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off)		
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in 20, quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) <120 watts (printing); < 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 H2), 2 A		
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP Designalet Universal Print Driver for HP-GL/2 and HP Designalet Universal Print Driver for HP-GL/2 and HP Designalet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 141 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 120 watts (printing); 2 watts (c 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC), Argentina (IRAM); Mexico		
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 114 kg (25.1 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in c2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 38 dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.0 B(A) (ready); < 3.4 B(A) (sleep) 6.8 B(A) (printing); 5.2 watts (c 7 watts with embedded Digital Front End) (sleep); 0 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant);		
(w x d x h) Weight What's in the box Environmental ranges Acoustic	Printer Shipping Printer Shipping HP DesignJet T3500 cartridges, stacker, s spindle adapter kit (s Operating temperature Storage temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	email printing HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI driver for Mac OS X; PostScript Windows and Mac drivers with optional PostScript/ PDF Upgrade Kit. Compatible with HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for HP-GL/2 and HP DesignJet Universal Print Driver for PS (with PostScript/PDF Upgrade Kit) 1400 x 784 x 1109 mm (55.1 x 30.9 x 43.7 in) 1502 x 780.5 x 804 mm (59.1 x 30.7 x 31.7 in) 141 kg (251 lb) 141 kg (310.8 lb) Production Multifunction Printer, printhead, introductory ink canner calibration sheet, printer stand and media bin, spindles, 3-in k2), quick reference guide, setup poster, startup software, power cord 5 to 40°C (41 to 104°F) -25 to 55°C (-13 to 131°F) 20 to 80% RH 50 dB(A) (printing); 3B dB(A) (ready); < 15 dB(A) (sleep) 6.8 B(A) (printing); 5.6 B(A) (ready); < 3.4 B(A) (sleep) 6.8 B(A) (printing); 2 watts (< 7 watts with embedded Digital Front End) (sleep); 0 watts (sfl) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); Korea (KC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China		

Ordering information

Product	B9E24A	HP DesignJet T3500 36-in Production Multifunction Printer9
	B9E24B	HP DesignJet T3500 36-in Production Multifunction Printer ¹⁰
Accessories	COC66A	HP DesignJet PostScript/PDF Upgrade Kit
	G8B09A	HP DesignJet T3500 36-in Spindle
	L3J69AAE	HP SmartStream Preflight Manager
	L3J71AAE	HP SmartStream Preflight Manager One-Year Subscription
	L3J78AAE	HP SmartStream Print Controller for HP DesignJet T3500 Production Multifunction Printer
Original HP printheads	B3P06A	HP 727 DesignJet Printhead
Original HP	C1Q13A	HP 764 300-ml Cyan DesignJet Ink Cartridge
ink cartridges	C1Q14A	HP 764 300-ml Magenta DesignJet Ink Cartridge
	C1Q15A	HP 764 300-ml Yellow DesignJet Ink Cartridge
	C1Q16A	HP 764 300-ml Matte Black DesignJet Ink Cartridge
	C1Q17A	HP 764 300-ml Photo Black DesignJet Ink Cartridge
	C1Q18A	HP 764 300-ml Gray DesignJet Ink Cartridge
Original HP large format printing	C6810A	HP Bright White Inkjet Paper (FSC® certified)¹¹ 🋟¹² 914 mm x 91.4 m (36 in x 300 ft)
materials	C6980A	HP Coated Paper (PEFC™ certified) ¹¹ 🏰² 914 mm x 91.4 m (36 in x 300 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ¹¹ 🎝 ¹² 914 mm x 30.5 m (36 in x 100 ft)
	Q1421B	HP Universal Satin Photo Paper 914 mm x 30.5 m (36 in x 100 ft)

Service and support¹³

H4518E	HP Installation Service with Network Setup
U1ZX9E	HP 3 year Next Business Day Onsite Support with DMR ¹⁴
U1ZY0E	HP 5 year Next Business Day Onsite Support with DMR ¹⁴
U1ZY1PE	HP 1 year Post Warranty, Next Business Day Onsite Support with DMR ¹⁴
U1ZY2PE	HP 2 year Post Warranty, Next Business Day Onsite Support with DMR ¹⁴
U1XV4E	HP Preventive Maintenance Service

HP DesignJet Support Services offer solutions for business critical environments – installation, extended support and maintenance, as well as variety of value-added services. For more information, please visit $\underline{\text{hp.com/go/Designjet/support.}}$

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays. 15 For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

Choose from a range of third-party solutions like OpCenter and SCP to streamline your digital printing and scanning operations.

- Compared with large-format color MFPs under \$25,000 USD. Based on the fastest-rated color speeds as published by manufacturers as of January 2014. Test methods vary
- Compared with large-format Low Volume LED MFPs with print speeds of up to 7 Arch D pages per
- Using HP SmartStream software, job preparation and processing can be completed in 50% of the time. Conclusion based on an HP internal test measuring the time required to extract pages from a 50-page document and print them using several printers compared with using equivalent software programs.
- Available when using HP SmartStream for DesignJet printers together with the HP DesignJet T3500 Production Multifunction Printer
- Mechanical printing time, Printed in Fast mode, using HP Bright White Inkiet Paper (Bond) and Original
- 6 +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.
- Measured on HP Matte Film.
- Based on 2.5 GB RAM.
- 90-day limited hardware warranty.
- ¹⁰ One-year limited hardware warranty.
- ¹¹ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. BMG trademark license code PEFC™/29-31-261, see pefc.org. HP trademark license code PEFC™/29-31-198, see pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.
- 12 Can be recycled through commonly available recycling programs.
- $^{\rm 13}$ HP Service portfolio available only for B9E24B HP DesignJet T3500 36-in Production Multifunction
- ¹⁴ Defective Media Retention keeps your sensitive data safe. To comply with security regulations you can keep the defective hard-drive or data-retentive memory component while getting a new replacement disk or memory.
- ¹⁵ True neutral grays produced by printers compatible with the HP Three-black ink set.

















For more information, please visit

hp.com/go/designjetT3500



